



IPC/VSL81

This fan less Vehicle VSL COMPACT81 generation is based on the Intel® Atom™ E3900 (formerly Apollo Lake) processor technology and offers a wide range of interface options. The robust and uncompromising industrial design allows the implementation in the most demanding IoT applications and guarantees long term availability.

- **Multi-core 64-bit Intel® Atom™ processor**
- **24/7 continuous operation**
- **M12 connector for Power and LAN**
- **Shock and vibration resistant**
- **Full -40...+85°C on component level**



Product Highlights

Power Ignition controller
 Trusted Platform Module - TPM2.0
 Inertial Measurement Unit (IMU)
 GPS with dead reckoning
 Fanless, No moving parts
 Maintenance free / Long term availability

Product Features

Intel® Atom™ E3900 Series
 up to 2.0GHz, up to 4 Cores
 RAM soldered on board up to 8GB
 Socket for CFast
 Ethernet, USB, CAN
 M12 connectors
 Stainless steel housing
 Protection class IP40
 LTE, GNSS, WiFi & Bluetooth options

Markets / Applications

Automotive
 Transportation
 Automated Guided Vehicles (AGV)
 Special purpose vehicles
 Agriculture
 Industrial trucks

Processor / Performance

Intel® Atom™ x7-E3950 2.00GHz (Burst) | 1.6GHz Clock - Quad Core

Intel® Atom™ x5-E3940 1.80GHz (Burst) | 1.6GHz Clock - Quad Core

Memory

L2 cache

2MB

RAM DDR3L 1866MT/s soldered on board

4GB

8GB DDR3 RAM¹

optional

Features

Inertial measurement unit (IMU) STMicroelectronics ISM330DHCXTR

Real time clock (RTC) with battery backup Renata CR2477N (950 mAh)

Hardware Watchdog & Temperature supervisor

Intelligent power management (Ignition controller)

TPM 2.0 according to ISO/IEC11889 Infineon SLB9665

Communication Interfaces

DisplayPort 1.4 (up to 7680 x 4320 @ 60Hz)

1

USB version 3.1

(Type A)

2

Ethernet 10/100/1000 Mbit (Intel I210-IT)

(M12 female x-coded)

2

PoE+ IEEE802.3at 10/100/1000Mbit requires taller housing: w228 x h85 x d127 mm

(M12 female x-coded)

optional

CAN 2.0A/B & CAN FD (PEAK FPGA chip, SJA1000 compatible) active/passive, isolated

(DSUB9)

2

CFast socket with retention frame²

1

M.2 Key B socket²

(3042)

1

M.2 Key E socket²

(2230)

1

Mini PCIe socket²

(full size)

1

MicroSD Card socket²

1

Buzzer

1

I2C bus²

1

Serial RS232²

2

Serial RS422/485, isolated

(DSUB9)

optional

HD Audio, Line in / out²

optional

Digital I/O, 24VDC (latency <1ms)

(4 inputs, 4 outputs)

optional

Analog input, 16bit resolution, voltage input: -10 ... +10V / 0 ... 30V Accuracy: +/- 0.1%

optional

Wireless Connectivity4G cellular module (3G/2G fallback) Sierra Wireless MC7455 - M2M only!
with dual nano SIM support

(2x SMA)

optional

GNSS positioning module with dead reckoning u-blox NEO-M9 Module

(1x SMA)

optional

Wireless LAN IEEE 802.11ac/a/b/g/n/ dual-band 2x2 MIMO SparkLAN WxxB-263ACNI(BT)

(2x RP-SMA)

optional

Technical Data

Exterior dimensions [mm]

w228 x h55 x d127

Net weight [gram]

~1750

Non-isolated input voltage, reverse polarity protected

(M12 4P male A-coded)

8.4 ... 45VDC

Current consumption typ. in mA @ 24V without Add-Ins, idle

~500

Power consumption typ. in Watt @ 24V without Add-Ins, idle

~12

Environmental ConditionsOperating temperature³

-40°C ... +70°C

Storage temperature

-40°C ... +85°C

Ingress Protection standard EN60529 (ISO 20653)

IP40

Road vehicles (UNECE-R10 "E-mark")

on request

Conformal coating⁴

on request

Shock

EN60068-2-27

Vibration

EN60068-2-64

EMI-Conformity

EN55032 / EN55035

Safety (designed to meet)

EN62368-1

Designed for ISO11783 compliant agricultural vehicles

•

Designed for EN 1175-1:1998+A1:2010 compliant industrial trucks

•

Radio and Telecommunication (designed to meet)

RED

MTBF @ 25°C according to Telcordia SR-332, Environment GB, excluding battery and optional extensions

~480 000h

¹ Please contact factory for minimum order quantities² Internal connector³ Depending on installation situation and interface connection. Please see user documentation.⁴ On all possible components (excl. Connectors and wireless devices)

Product specifications subject to change without notice. | All data is for information purposes only and not guaranteed for legal purposes. Information in this data sheet has been carefully checked and is believed to be accurate. However, no responsibility is assumed for inaccuracies. Please refer to the user documentation for additional product specification.